



FLANGE DUAL DRILLED  
 BS4504 PN6/PN10  
 4-HOLES Ø14 EQUI-SPACED DN A  
 110 PCD  
 4-HOLES Ø19 EQUI-SPACED DN A  
 125 PCD

NOTE :-

- 1) PUMP SHAFT MUST BE MOUNTED HORIZONTALLY
- 2) FOR CORRECT ORIENTATION REFER TO D & M INSTRUCTIONS

1 x 230V	POWER	FLC
50Hz IEC38	WATT	Amps
AUTD MIN.	60	0.40
AUTD MAX.	700	4.60
SPEED 1-4	300-700	2.0-4.60
NPSH (bar)	80°C-0.5	95°C-1.5

LAST MODIFICATION DETAILS

ISSUE	DATE	DRN	APP
A	CHK	-	-

ALL DIMENSIONS IN mm  
 DRAWN TO BS308  
 WELDING SYMBOLS TO BS499  
 SURFACE FINISH SHOWN IN MICROMETERS  
 MACHINE WHERE SHOWN TO TOLERANCE ± 0.3MM UNLESS OTHERWISE STATED

JOB No.	PART No.	WEIGHT KG	FILE NAME
-	-	19.6	-
DESIGN No.	PATTERN No.	MATERIAL	MAT'L SPEC.
-	-	-	-

TITLE  
 GENERAL ARRANGEMENT  
 AGE+50-140-1 PUMP

DRG No.	AGE501401
DATE	02/03/2011
CHK	BSD
SCALE	1:1
DRN	BSD
APP	PK
SHEET	1 OF 1



VENLDOCK WAY, MANCHESTER, M12 5JL  
 TEL: +44 (0) 161 223 2223