



FLANGE DRILLED
 BS4504 PN10
 8-HOLES Ø18 EQUI-SPACED DN A
 160 PCD

NOTE :-
 1) PUMP SHAFT MUST BE MOUNTED HORIZONTALLY
 2) FOR CORRECT ORIENTATION REFER TO D & M INSTRUCTIONS

1 x 230V	POWER	FLC
50Hz IEC38	WATT	AmPds
AUTD MIM.	150	1.30
AUTD MAX.	1400	9.00
SPEED 1-4	800-1400	5.7-9.00
NPSH (bar)	80°C-0.5	95°C-1.5

LAST MODIFICATION DETAILS		ALL DIMENSIONS IN mm		JOB No.		PART No.		WEIGHT KG		FILE NAME	
DRAWN TO BS308		WELDING SYMBOLS TO BS499		DESIGN No.		PATTERN No.		MATERIAL		MATERIAL SPEC.	
SURFACE FINISH SHOWN IN MICROMETERS		MACHINE WHERE SHOWN TO TOLERANCE ± 0.3MM UNLESS OTHERWISE STATED		-		-		-		-	
ISSUE DATE	DRN	THIS DRAWING IS THE PRIVATE AND CONFIDENTIAL PROPERTY OF ARMSTRONG HOLDEN BROOKE PULLEN LTD. ALL COPYRIGHT, MANUFACTURING AND SALES RIGHTS RESERVED.									
A	CHK	APP	TITLE								
			GENERAL ARRANGEMENT								
			AGE+80-120-1 PUMP								
DATE		DRN	AGE801201		DATE		03/03/2011	DRN		BSD	
SCALE		1:1	SHEET		1	OF		1		OF	
ARMSTRONG											
VENLDOCK WAY, MANCHESTER, M12 5JL TEL: +44 (0) 161 223 2223											