



FLANGE DUAL DRILLED
 BS4504 PN6/PN10
 4-HOLES Ø14 EQUI-SPACED DN A
 110 PCD
 4-HOLES Ø18 EQUI-SPACED DN A
 125 PCD

1 x 230V	POWER	FLC
50Hz IEC38	W/ATT	Amps
AUTO MIN.	60	0.40
AUTO MAX.	700	4.60
SPEED 1-4	300-700	2.0-4.60
NPSH (bar)	80°C-0.5	95°C-1.5

NOTE :-
 1) PUMP SHAFT MUST BE MOUNTED HORIZONTALLY
 2) FOR CORRECT ORIENTATION REFER TO D & M INSTRUCTIONS

LAST MODIFICATION DETAILS		JOB No.		PART No.		WEIGHT KG		FILE NAME		TITLE	
DRAWN TO BS308		-		-		34.14		-		GENERAL ARRANGEMENT	
WELDING SYMBOLS TO BS499		DESIGN No.		PATTERN No.		MATERIAL		MAT'L SPEC.		AGET+50-140-1 PUMP	
SURFACE FINISH SHOWN IN		-		-		-		-		DRG No. AGT501401	
MICROMETERS		-		-		-		-		DATE 04/03/2011	
MACHINE WHERE SHOWN ✓		-		-		-		-		DRN BSD	
TO TOLERANCE ± 0.3MM		-		-		-		-		APP PK	
UNLESS OTHERWISE STATED		-		-		-		-		SCALE 1:1	
ISSUE DATE		-		-		-		-		SHEET 1 OF 1	
A		-		-		-		-		VENLOCK WAY, MANCHESTER, M12 5JL	
A		-		-		-		-		TEL: +44 (0) 161 223 2223	

