



FLANGE DRILLED
 BS4504 PN10
 8-HOLES Ø138 EQUI-SPACED 160 PCD
 DN A

NOTE :-
 1) PUMP SHAFT MUST BE MOUNTED HORIZONTALLY
 2) FOR CORRECT ORIENTATION REFER TO D & M INSTRUCTIONS

| | | |
|------------|----------|----------|
| 1 x 230V | POWER | FLC |
| 50Hz IEC38 | W/ATT | Amps |
| AUTO MIM. | 150 | 1.30 |
| AUTO MAX. | 1400 | 9.00 |
| SPEED 1-4 | 800-1400 | 5.7-9.00 |
| NPSH (bar) | 80°C-0.5 | 95°C-1.5 |

| | | | | | | | | |
|--|-------|------------|-------------|----------|-------------|--------------------|--|--|
| LAST MODIFICATION DETAILS | | JOB No. | | PART No. | WEIGHT KG | FILE NAME | TITLE | |
| DRAWN TO BS308 WELDING SYMBOLS TO BS499 SURFACE FINISH SHOWN IN MICROMETERS MACHINE WHERE SHOWN ✓ TO TOLERANCE ± 0.3MM UNLESS OTHERWISE STATED | | - | - | - | 67.5 | - | GENERAL ARRANGEMENT AGET+80-120-1 PUMP | |
| ISSUE DATE | DRN - | DESIGN No. | PATTERN No. | MATERIAL | MAT'L SPEC. | DRG No. AGET801201 | | |
| A | CHK - | APP - | | | | DATE 0/03/2011 | DRN BSD | |
| | | | | | | CHK BSD | APP PK | |
| | | | | | | SCALE 1:1 | SHEET 1 OF 1 | |
| THIS DRAWING IS THE PRIVATE AND CONFIDENTIAL PROPERTY OF ARMSTRONG HOLDEN BROOKE PULLEN LTD. ALL COPYRIGHT, MANUFACTURING AND SALES RIGHTS RESERVED. | | | | | | | | |
| | | | | | | | VENLUDOK WAY, MANCHESTER, M12 5JL TEL: +44 (0) 161 223 2223 | |