



EXCHANGER SIZE	DIMENSIONS											
	A		B		C		D		(N1)		(N2)	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
WSX-123-2E2	63 5/8	1616	37	940	26	660	40	1016	6	152	2	51
WSX-124-2E2	75 5/8	1921	49	1245	38	965	52	1321	6	152	2	51
WSX-125-2E2	87 5/8	2226	61	1549	50	1270	64	1626	6	152	2	51
WSX-126-2E2	99 5/8	2530	73	1854	62	1575	76	1930	6	152	2	51
WSX-127-2E2	111 5/8	2835	85	2159	74	1880	88	2235	8	203	2 1/2	64
WSX-128-2E2	123 5/8	3140	97	2464	86	2184	100	2540	8	203	2 1/2	64
WSX-129-2E2	135 5/8	3445	109	2769	98	2489	112	2845	8	203	2 1/2	64
WSX-1210-2E2	147 5/8	3750	121	3073	110	2794	124	3150	8	203	2 1/2	64
WSX-1211-2E2	159 5/8	4054	133	3378	122	3099	136	3454	8	203	2 1/2	64
WSX-1212-2E2	171 5/8	4359	145	3683	134	3404	148	3759	8	203	2 1/2	64
WSX-1213-2E2	183 5/8	4664	157	3988	146	3708	160	4064	8	203	2 1/2	64
WSX-1214-2E2	195 5/8	4969	169	4293	158	4013	172	4369	8	203	2 1/2	64
WSX-1215-2E2	207 5/8	5274	181	4597	170	4318	184	4674	8	203	2 1/2	64

NOZZLE SCHEDULE				
SERVICE	MARK	SHELL SIDE	MARK	TUBE SIDE
INLET	(N1)	AS PER TABLE	(N5)	4 (102) FLG
OUTLET	(N2)	AS PER TABLE	(N6)	4 (102) FLG
DRAIN	(N3)	1/2 (13) NPT		
VENT	(N4)	3/4 (19) NPT		

NOTES: 1. SUPPORTS SUPPLIED ONLY IF SPECIFIED ON ORDER.
 2. NOZZLE SIZES SHOWN ARE RECOMMENDED FOR MAXIMUM EXCHANGER LIFE.
 3. FABRICATED TO ASME CODE SECTION VIII DIVISION 1 AND LATEST ADDENDA.
 4. DRAWING IS NOT TO SCALE.
 5. ALL DIMN'S ±1/8 (3) UNLESS OTHERWISE SHOWN.

DESIGN CONDITIONS				
	SHELL		TUBES	
DESIGN PRESSURE	150 PSIG	1034 KPa	150 PSIG	1034 KPa
DESIGN TEMPERATURE	375 °F	191 °C	375 °F	191 °C
MIN. DESIGN METAL TEMP.	35 °F	1.7 °C	35 °F	1.7 °C
HYDRO. TEST PRESSURE	225 PSIG	1551 KPa	300 PSIG	2068 KPa
CONTENTS	STEAM		WATER	

CUSTOMER:
 LOCATION:
 ENGINEER:
 ORDER No.:
 PROJECT/JOB:
 LOCATION:
 TAG: (QUOTE #)

TITLE	G.A. 150 LB. WSX SERIES HEAT EXCHANGERS				A R M S T R O N G				NUMBER	REV.
DATE:	12 / 01 / 94	BY:	D.C.R.	TORONTO - CANADA	MONTREAL - CANADA	BUFFALO - N. Y.	COLCHESTER - U.K.	WSX-12-2P-E2		
				TEL : (416) 755-2291	TEL : (514) 421-2424	TEL : (716) 693-8813	TEL : (44) 120-657-9491			