



EXCHANGER SIZE	DIMENSIONS											
	A		B		C		D		(N1)		(N2)	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
WSX-168-2-2	112 3/4	2864	79 3/4	2026	66	1676	100	2540	10	254	3	76
WSX-169-2-2	124 3/4	3169	91 3/4	2330	78	1981	112	2845	10	254	3	76
WSX-1610-2-2	136 3/4	3473	103 3/4	2635	90	2286	124	3150	10	254	3	76
WSX-1611-2-2	148 3/4	3778	115 3/4	2940	102	2591	136	3454	10	254	3	76
WSX-1612-2-2	160 3/4	4083	127 3/4	3245	114	2896	148	3759	10	254	3	76
WSX-1613-2-2	172 3/4	4388	139 3/4	3550	126	3200	160	4064	10	254	3	76
WSX-1614-2-2	184 3/4	4693	151 3/4	3854	138	3505	172	4369	10	254	3	76
WSX-1615-2-2	196 3/4	4997	163 3/4	4159	150	3810	184	4674	10	254	3	76

NOZZLE SCHEDULE				
SERVICE	MARK	SHELL SIDE	MARK	TUBE SIDE
INLET	(N1)	AS PER TABLE	(N5)	6 (152) FLG
OUTLET	(N2)	AS PER TABLE	(N6)	6 (152) FLG
DRAIN	(N3)	1/2 (13) NPT		
VENT	(N4)	3/4 (19) NPT		

**NOTES:** 1. SUPPORTS SUPPLIED ONLY IF SPECIFIED ON ORDER.  
 2. NOZZLE SIZES SHOWN ARE RECOMMENDED FOR MAXIMUM EXCHANGER LIFE.  
 3. FABRICATED TO ASME CODE SECTION VIII DIVISION 1 AND LATEST ADDENDA.  
 4. DRAWING IS NOT TO SCALE.  
 5. ALL DIM'S ±1/8 (3) UNLESS OTHERWISE SHOWN.

DESIGN CONDITIONS				
	SHELL		TUBES	
DESIGN PRESSURE	150 PSIG	1034 KPa	150 PSIG	1034 KPa
DESIGN TEMPERATURE	375 °F	191 °C	375 °F	191 °C
MIN. DESIGN METAL TEMP.	40 °F	4.4 °C	40 °F	4.4 °C
HYDRO. TEST PRESSURE	225 PSIG	1551 KPa	300 PSIG	2068 KPa
CONTENTS	STEAM		WATER	

CUSTOMER:  
 LOCATION:  
 ENGINEER:  
 ORDER No.:  
 PROJECT/JOB:  
 LOCATION:  
 TAG: (QUOTE # )

TITLE G.A. 150 LB. WSX SERIES HEAT EXCHANGERS	A R M S T R O N G				NUMBER	REV.
DATE: 12/01/94	BY: D.C.R.	TORONTO - CANADA TEL: (416) 755-2291	MONTREAL - CANADA TEL: (514) 421-2424	BUFFALO - N. Y. TEL: (716) 693-8813	COLCHESTER - U.K. TEL: (44) 120-657-9491	WSX-16-2P-2(10)