



DIMENSIONS SHOWN AS: inches (mm)

EXCHANGER SIZE *BAFFLE SPACING	DIMENSIONS											
	A		B		C		D		N1		N2	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
WX-62-2*-2	31 5/8	803	16	406	7	178	26	660	3	76	3	76
WX-63-2*-2	43 5/8	1108	28	711	19	483	38	965	3	76	3	76
WX-64-2*-2	55 5/8	1413	40	1016	31	787	50	1270	3	76	3	76
WX-65-2*-2	67 5/8	1718	52	1321	43	1092	62	1575	3	76	3	76
WX-66-2*-2	79 5/8	2022	64	1626	55	1397	74	1880	3	76	3	76
WX-67-2*-2	91 5/8	2327	76	1930	67	1702	86	2184	3	76	3	76
WX-68-2*-2	103 5/8	2632	88	2235	79	2007	98	2489	3	76	3	76
WX-69-2*-2	115 5/8	2937	100	2540	91	2311	110	2794	3	76	3	76
WX-610-2*-2	127 5/8	3242	112	2845	103	2616	122	3099	3	76	3	76
WX-611-2*-2	139 5/8	3546	124	3150	115	2921	134	3404	3	76	3	76
WX-612-2*-2	151 5/8	3851	136	3454	127	3226	146	3708	3	76	3	76

NOZZLE SCHEDULE				
SERVICE	MARK	SHELL SIDE	MARK	TUBE SIDE
INLET	N1	AS PER TABLE	N5	2 (51) NPT
OUTLET	N2	AS PER TABLE	N6	2 (51) NPT
DRAIN	N3	1/2 (13) NPT		
VENT	N4	3/4 (19) NPT		

NOTES:

1. SUPPORTS SUPPLIED ONLY IF SPECIFIED ON ORDER.
2. NOZZLE SIZES SHOWN ARE RECOMMENDED FOR MAXIMUM EXCHANGER LIFE.
3. FABRICATED TO ASME CODE SECTION VIII DIVISION 1 AND LATEST ADDENDA.
4. DRAWING IS NOT TO SCALE.
5. ALL DIMN'S ±1/8 (3) UNLESS OTHERWISE SHOWN.

DESIGN CONDITIONS				
	SHELL		TUBES	
DESIGN PRESSURE	150 PSIG	1034 KPa	150 PSIG	1034 KPa
DESIGN TEMPERATURE	375 °F	191 °C	375 °F	191 °C
MIN. DESIGN METAL TEMP.	35 °F	1.7 °C	35 °F	1.7 °C
HYDRO. TEST PRESSURE	225 PSIG	1551 KPa	300 PSIG	2068 KPa
CONTENTS	WATER		WATER	

CUSTOMER:
LOCATION:
ENGINEER:
ORDER No.:
PROJECT/JOB:
LOCATION:
TAG: (QUOTE #)

TITLE	G.A. 150 LB. WX SERIES HEAT EXCHANGERS	A R M S T R O N G				NUMBER	WX-6-2P-2(3)	REV.			
DATE:	12 / 01 / 94	BY:	D.C.R.	TEL :	(416) 755-2291	MONTREAL - CANADA	TEL : (514) 421-2424	BUFFALO - N. Y.	TEL: (716) 693-8813	COLCHESTER - U.K.	TEL: (44) 120-657-9491